

**HAMPTON™**

## Hinge Joint

All our fences are manufactured to BS EN 10223 and unless otherwise requested, all wires used are manufactured to BS4102 and galvanised to BS EN 10244-2 Class A. This brings our hinge joint fences within the scope of the Natural England Catchment Sensitive Farming Capital Grant Scheme.

Furthermore we recognise that our customers are professionals who understand their own requirements and who need to buy with confidence and ease.



### A choice of grades

- L** Lighter grade fence for less demanding or temporary jobs
- C** Medium grade fence very popular for standard applications
- B** Heavy duty grade
- LHT** Lighter high tensile for applications where additional fence strength is required
- HT** Full high tensile where the strongest fence is required

### Features

- **Cost effective** – traditional, durable fencing solution
- **Labour efficient** – larger 500 metre rolls available
- **Flexibility** – hinge design allows fence to flex under pressure but still retain its form
- **Choice** – wide range of industry recognised patterns can be manufactured quickly to suit most applications
- **Eco friendly** – 100% recyclable

## Wire Gauges and Tensile Strengths by Fence Grade

Grade	Top & Bottom Line Wires		Intermediate Line Wires		Stay Wires	
	Nominal Wire Dia. (mm)	Minimum Tensile Strength (N/mm <sup>2</sup> )	Nominal Wire Dia. (mm)	Minimum Tensile Strength (N/mm <sup>2</sup> )	Nominal Wire Dia. (mm)	Minimum Tensile Strength (N/mm <sup>2</sup> )
L	2.50	600	2.00	600	2.00	600
C	3.00	600	2.50	600	2.50	600
B	4.00	600	3.00	600	3.00	350
LHT	2.00	1050	2.00	1050	2.00	600
HT	2.50	1050	2.50	1050	2.50	600

Do not forget the wide range of customer specifiable fence lengths at your disposal, with many patterns available in jumbo, **500m length rolls**.