

Galvanised Chain Link Fencing

- Easy to roll out and erect
- Confidence and assurance that you have purchased one of the best chain link systems available
- Available with knuckled or barbed ends
- Supplied with line wires as standard
- Manufactured to BS EN 10223-6
- Wire produced to BS 4102
- Wire galvanised to BS EN10244-2 Class A
- 50mm mesh as standard
- Other mesh sizes available
- Available in low (under 600N/mm²) or high (over 600N/mm²) tensile formats and now 1050N/mm²(min)

Wire Diameters (mm)	2.50	3.00	3.55	3.15
Tensile Strength	Low/High	Low/High	Low/High	1050 N/mm ² (min.)
Typical Heights (mm)	Standard Roll Lengths (metres)			
900	25	25	12.5	25
1050	25	25	12.5	25
1200	25	25	12.5	25
1400	25	12.5 / 25	12.5	12.5
1500	25	12.5 / 25	12.5	12.5
1800	25	12.5 / 25	12.5	12.5
2000	12.5	12.5	12.5	12.5
2100	12.5	12.5	12.5	12.5
2150	12.5	12.5	12.5	12.5
2400	12.5	12.5	12.5	12.5
2750	12.5	12.5	12.5	12.5
3000	12.5	12.5	12.5	12.5
3050	12.5	12.5	12.5	12.5
3600	12.5	12.5	12.5	12.5