

Sentinel®

Hinge Joint Fencing

All our fences are manufactured to BS EN 10223 and unless otherwise requested, all wires used are manufactured to BS4102 and galvanised to BS EN 10244-2 Class A.

All Hampton's Sentinel fencing is guaranteed for 10 years, terms and conditions apply.

Furthermore we recognise that our customers are professionals who understand their own requirements and who need to buy with confidence and ease.



A choice of grades

L	Lighter grade fence for less demanding or temporary jobs
C	Medium grade fence very popular for standard applications
B	Heavy duty grade
LHT	Lighter high tensile for applications where additional fence strength is required
HT	Full high tensile where the strongest fence is required

Features

- **Cost effective** – traditional, durable fencing solution
- **Labour efficient** – larger 500 metre rolls available
- **Flexibility** – hinge design allows fence to flex under pressure but still retain its form
- **Choice** – wide range of industry recognised patterns can be manufactured quickly to suit most applications
- **Eco friendly** – 100% recyclable

Wire Gauges and Tensile Strengths by Fence Grade

Grade	Top & Bottom Line Wires		Intermediate Line Wires		Stay Wires	
	Nominal Wire Dia. (mm)	Minimum Tensile Strength (N/mm ²)	Nominal Wire Dia. (mm)	Minimum Tensile Strength (N/mm ²)	Nominal Wire Dia. (mm)	Minimum Tensile Strength (N/mm ²)
L	2.50	695	1.90	695	1.90	695
C	3.00	695	2.50	695	2.50	695
B	4.00	695	3.00	695	3.00	415
LHT	2.00	1100	2.00	1100	2.00	695
HT	2.50	1235	2.50	1235	2.50	695

Do not forget the wide range of customer specifiable fence lengths at your disposal, with many patterns available in jumbo, 500m length rolls.

